



RP-880

Thermal Receipt Printer

# Specification

## standard

**printing method** : direct thermal

**print speed** : 150mm/s

**resolution** : 203dpi

**print width** : 80mm

**memory**: 1MB Flash (128kB user)

128kB RAM (16kB user)

**drivers** : win98, NT, win2000, XP, OPOS

**cashdrawer port** : RJ11, 12 / 24V

**cutter** : full cut, partial cut

**fonts** : standard 13x24, compressed 9x17

**barcodes**: I2of5, UPC-A, EAN-13, UPC-E, EAN-8, STD25, Codabar, Code39, Code128

**code pages** : 437, 850, 852, 858, 860, 863, 865, 866

## reliability

**printhead** : min 100km printed lines

**cutter** : 1,000,000 cuts

**MCBF** : 52,000,000 lines

## media

**paper width** : 80mm standard  
(56,60,62,72, 82mm adjustable)

**paper density** : 100gsm max

**paper roll diameter** : 90mm max

## options

- available in black, white or silver
- serial RS232, parallel Centronics, USB interface
- Ethernet interface
- WLAN interface
- powered USB cable
- spill proof cover
- cable cover
- wall mount bracket

## dimensions

**size** : 142 w x 192 d x 139 h mm

Cable Cover



WLAN interface

